

SlideRenu®

PRODUCT COMPARISONS: CLEANERS

MAINTENANCE SOAP

HEAVY DUTY DE-GREASER

PERFORMANCE CHARACTERISTICS Y=YES / N=NO	SLIDERENU SLIDESOAP	3M MARINE BOAT SOAP	NATIONAL BRANDS	SLIDERENU SLIDEDETERGENT	3M MARINE BOAT SOAP	NATIONAL BRANDS
REMOVES:						
- Grease	Y	Y	Y	Y	Y	Y
- Grime	Y	Y	Y	Y	Y	Y
- Bird Droppings	Y	Y	Y	Y	Y	Y
- Leaf Stains	N	N	N	Y	N	N
- Water Shoe Marks	N	N	N	Y	N	N
- Rust Stains	N	N	N	Y	N	N
- Body Oils	Y	Y	Y	Y	Y	Y
- Suntan Lotions	Y	Y	Y	Y	Y	Y
- Zinc Oxide Sunscreen	N	N	N	Y	N	N
Environmentally Safe / Biodegradable / VOC Compliant	Y	Y	Y/N	Y	Y	Y/N
Worker Safe	Y	Y	Y/N	Y	Y	Y/N
Foam Cleaning Surfactant Technology	Y	N	N	NA	NA	NA
Penetrating Nano-Surfactant Technology	NA	NA	NA	Y	N	N
Specifically Formulated for Water Slide Surfaces	Y	N	N	Y	N	N
May Cause Damage to Water Slide Surface	N	N	Y/N	N	N	Y/N
Cost per Seasonal Application / 100' x 36" Water Slide	\$10	\$35	\$15	\$45	\$35	\$15

SlideCare, LLC

SlideRenu® is a Registered Trademark of SlideCare, LLC

3428 Napa Boulevard Suite 1971 • Avon, Ohio 44011

Tel: 216.503.7203 / 440.781.0051 • Fax: 440.930.2490

www.sliderenu.com

REVISED 6/11

SlideRenu®

PRODUCT COMPARISONS: WAXES

BUFFING WAX

SPRAYABLE WAX

PERFORMANCE CHARACTERISTICS Y=YES / N=NO	SLIDERENU SLIDEWAX	3M MARINE WAX	TURTLE WAX HARD SHELL	SLIDERENU SLIDEGLOSS	3M MARINE WAX	TURTLE WAX HARD SHELL
High-Speed Buffing Machine Recommended	Y	N	N	N	N	N
Contains Nano-technology Polymers Recommended for Water Slides	Y	N	N	Y	N	N
Requires More Than One Coat of Protection	N	Y	Y	Y	Y	Y
Lasts Longer Than 3 Months / 100 Day Operating Season*	Y	N	N	N	N	N
Super High Luster / Wet Look Shine	N	N	N	Y	N	N
Chorine Resistant Formula	Y	N	N	Y	N	N
Abrasion Resistant Formula	Y	N	N	Y	N	N
Environmentally Safe / Biodegradable / VOC Compliant	Y	Y	Y	Y	Y	Y
Worker Safe	Y	Y	Y	Y	Y	Y
Specifically Formulated for Water Slide Surfaces	Y	N	N	Y	N	N
May Cause Damage to Water Slide Surface	N	Y/N	Y/N	N	Y/N	Y/N
Cost per Seasonal Application / 100' x 36" Water Slide	\$160	\$130	\$120	\$100	\$130	\$120

* Severely oxidized slides and slides +5 years old will not hold their wet-look shine for more than 2 weeks after waxing.

SlideCare, LLC

SlideRenu® is a Registered Trademark of SlideCare, LLC

3428 Napa Boulevard Suite 1971 • Avon, Ohio 44011

Tel: 216.503.7203 / 440.781.0051 • Fax: 440.930.2490

www.sliderenu.com

REVISED 6/11

SlideRenu®

PRODUCT COMPARISONS: DE-SCALERS

SCALE REMOVER

POLISHING COMPOUND

PERFORMANCE CHARACTERISTICS Y=YES / N=NO	SLIDERENU CALCITROL	CLR	NATIONAL BRANDS	SLIDERENU SLIDEPOLISH	3M RUBBING COMPOUND	TURTLE WAX RUBING COMPOUND
REMOVES:						
- Calcium Carbonite	Y	Y	Y/N	N	N	N
- Calcium Silicate	Y	Y	Y/N	N	N	N
- Hard Water Mineral Deposits	Y	Y	Y/N	N	N	N
- Salt Residue	Y	Y	Y/N	Y	Y	Y/N
- Surface Oxidation*	N	N	N	Y	Y	Y/N
Contains Surface Damaging Phosphoric Acid / Emits Toxic Fumes	N	Y	Y	N	N	N
Environmentally Safe / Biodegradable / VOC Compliant	Y	N	N	Y	Y	Y
Worker Safe	Y	N	N	Y	Y	Y
Specifically Formulated for Water Slide Surfaces	Y	N	N	Y	N	N
May Cause Damage to Water Slide Surface	N	Y	Y	N	Y	Y
Cost per Seasonal Application / 100' x 36" Water Slide	\$60	\$50	\$40	\$120	\$80	\$60

* Severe impregnated oxidation permanently damages the color pigment and cannot be rejuvenated. To bring back the like-new appearance requires the surface to be refinished with a film forming coating.

SlideCare, LLC

SlideRenu® is a Registered Trademark of SlideCare, LLC

3428 Napa Boulevard Suite 1971 • Avon, Ohio 44011

Tel: 216.503.7203 / 440.781.0051 • Fax: 440.930.2490

www.sliderenu.com

SlideRenu®

WATER SLIDE WAXING PROCEDURE

The following procedure has been developed by SlideCare, LLC and is provided to our customers who choose to restore their own slides using our cleaners, polishing compounds and waxes. They have been established based on years of experience in restoring the LIKE-NEW and WET-LOOK shine to dull color faded water slides and aquatic play structures.

1. If the interior slide joints are not permanently sealed, remove only worn or loose caulk from the interior slide joints using a utility knife. Properly dispose of used caulk according to local regulations.

2. Clean all surfaces to be restored with SlideDetergent™ using a spray bottle and scrub brush. Refer to the SlideDetergent™ label for the proper amount to use, the agitation method and work time. Always clean the slide starting from the bottom working your way up to the top of the slide.

3. Rinse the slide starting at the top of the slide working your way down to the bottom of the slide with clean potable water through a pressure washer. To obtain professional results, we recommend a HOT WATER 3,500 PSI pressure washer be used when rinsing the slide.

4. Remove all hard water mineral deposits, oxidation, water lines and calcium scale build-up with SlideRenu® Calcitrol™. Wet sand with 180-220 grit sandpaper while spraying Calcitrol™ to remove heavy scale build-up. Refer to the Calcitrol™ label for the proper amount to use, the agitation method and work time.

5. Rinse the slide starting at the top of the slide working your way down to the bottom of the slide with clean potable water through a pressure washer.

6. After the slide is dry and if the interior slide joints are not permanently sealed, lightly sand the joints to be caulked with 100 grit size sandpaper and remove the surface dust with a wet MEK

(Methyl Ethyl Ketone) solvent white cotton cloth.

7. Caulk the interior joints with either SlideRenu® SlideCaulk™, SikaFlex 291 Fast Cure, 3M 5200 Adhesive Sealant or permanently seal the joints with SlideRenu® PermaJoint Sealer™. Properly dispose of empty caulk tubes according to local regulations.

8. Using a variable high-speed polishing machine and a wool pad, polish the slide with SlideRenu® SlidePolish™ to remove deep impregnated oxidation and surface stains. To remove the toughest oxidation and stains, use 180-220 grit wet sandpaper while applying SlidePolish™. Refer to the SlidePolish™ label for the proper amount to use, the agitation method and work time.

9. Rinse the slide starting at the top of the slide working your way down to the bottom of the slide with clean potable water through a garden hose. It is recommended that a de-ionized water filter be attached to the water supply hose during the final rinse in order to effectively remove the final dust-polish film and remaining surface contaminants prior to the application of any SlideRenu® waxes.

10. Using a variable high-speed polishing machine and a foam finishing pad, wax the interior slide surface and seams with SlideRenu® SlideWax™ or SlideGloss™ in accordance with label instructions.*

11. DO NOT OPERATE THE SLIDE FOR 4-6 HOURS TO ENSURE THE WAX HAS PROPERLY HARDENED.

Please contact us through our website at www.sliderenu.com if you have any questions while performing these procedures.

* Severely oxidized slides and slides +5 years old will not hold their wet-look shine for more than 2 weeks after waxing.

SlideCare, LLC

3428 Napa Boulevard Suite 1971 • Avon, Ohio 44011
Tel: 216.503.7203 / 440.781.0051 • Fax: 440.930.2490
www.sliderenu.com

REVISED 12/11