

# SlideRenu®

## PRODUCT DATA SHEET

# SLIDEGLAZE™

## CLEAR WATER SLIDE PROTECTANT

### DESCRIPTION

SlideGlaze™ is a revolutionary aquatics maintenance product that brings back the "LIKE NEW WET LOOK SHINE" to dull color faded fiberglass water slides. It has been specially formulated to produce a hard shield of protection and "LONG LASTING" wet look shine to dull color faded fiberglass water slides that lasts the entire operating season. SlideGlaze™ rehydrates oxidized surfaces to bring back a deep reflective luster and "WET LOOK SHINE" to weathered looking water slides and fiberglass aquatic structures.

SlideGlaze™ is not a wax, polish, compound or paint. It requires no rubbing, buffing, cure time or unique application tools. With limited instructions, it can be easily applied by your internal maintenance staff and seasonal employees. SlideGlaze™ significantly outperforms carnauba, car and marine waxes. It will not wash off or be affected by routine soap and water cleaning processes. Depending on rider usage, geographic location and weather conditions, one protective application (2 coats) typically lasts up to 3-4 months. One gallon yields 2 protective coats which will rejuvenate the interior surface of a standard 100 linear foot open flume body slide, roughly 1,000 sq. ft. A minimum of 2 protective coats is required to bring back the "LIKE NEW SHINE" but 3-4 coats are recommended on any slide surface to obtain a "LONG LASTING WET LOOK" that will last the entire operating season. To protect the glide path, 5 protective coats are recommended.

### RECOMMENDED USES

SlideGlaze™ is recommended to be used on interior riding surfaces and the exterior skin of water slides to protect and enhance appearance. SlideGlaze™ is a clear liquid fiberglass glaze product that produces a "LONG LASTING WET LOOK SHINE" that can be used anytime a slide is looking dull, in need of surface protection or to reduce static charge and friction on the ride path. To reapply, clean surface with SlideRenu® SlideSoap™ (Refer to Product Data Sheet for Application Instructions), let dry and apply SlideGlaze™.

### DIRECTIONS FOR USE

For SlideGlaze™ to be effective, the product must be applied to a clean and adequately prepped surface. Any dirt, grease, body-grime, bird droppings, wax, surface oxidation and other surface contaminants should be removed first with SlideRenu® SlideDetergent™ (Refer to Product Data Sheet for Application Instructions). After the surface is washed, it should be rinsed with potable quality water through a pressure washer. To remove calcium build-up and hard water mineral deposits, use SlideRenu® Calcitrol™ (Refer to Product Data Sheet for Application Instructions). Rinse the surface with water after using

Calcitrol™. Let dry and apply SlideGlaze™. To remove extremely heavy oxidation wet sand with 1000 grit sand paper. Rinse and let dry. Shake SlideGlaze™ well before each application. Apply SlideGlaze™ directly and evenly onto the SlideRenu® applicator pad. Do not saturate the pad. Apply SlideGlaze™ much like you would paint in thin overlapping strokes. Do not press down on the pad during application as this will create bubbles and runs. Drips and runs should be removed immediately with the applicator before they can dry. Due to abrasion from riders and constant water flow, a minimum of 5 thin coats are recommended on the glide path. When layering SlideGlaze™, let the first coat dry at least 3 minutes before applying the next coat. Each successive coat extends the longevity of the "WET LOOK SHINE" and the self-leveling properties of SlideGlaze™. Do not apply if the temperature will drop below 40° F. within 24 hours following application. The applicator should be washed with clean water after each use and stored in an airtight bag for future use. Do not let applicator dry out.

### PROPERTIES

- APPEARANCE: Milky Bland Liquid
- ODOR: Slight Ammonia Scent
- COVERAGE: 1 Gallon Yields 2 Protective Coats Which Will Cover the Interior Surface of a 100' Open Body Slide; Approximately 1,000 sq. ft.
- VOC's: None
- PH: 8.0 - 8.5
- SHELF LIFE: 12 Months. Keep From Freezing.
- APPLICATION TEMPERATURE: 50F – 100F.
- FLAMMABLE: No
- BIODEGRADABLE: Yes

### DO NOT MIX THIS PRODUCT WITH ANY OTHER CHEMICALS

### CAUTION: KEEP OUT OF REACH OF CHILDREN

Eye and skin irritant. In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. CONTACT PHYSICIAN IMMEDIATELY.

**This product is available in 1 Gallon bottles and sold exclusively by SlideCare, LLC.**

### SlideCare, LLC

3428 Napa Boulevard Suite 1971 • Avon, Ohio 44011  
Tel: 216.503.7203 / 440.781.0051 • Fax: 440.930.2490

[www.sliderenu.com](http://www.sliderenu.com)



Environmentally  
Friendly